




SRL Series 2.7V -40~+70°C

■ Features

- Lower ESR
- Low temperature
- RoHS compliant
- Consumer electronic
- Pulse power
- Hold-up power



Items	Characteristics		
Rated Voltage	2.7V		
Operating Temperature Range	-40 ~+70°C	(-40 ~+85°C @2.3V)	
Surge Voltage	2.85V		
Capacitance Range	1~100 F		
Capacitance Tolerance (25°C)	-10~+30%		
Temperature Characteristics	The specifications shall be met at category temperature range from -40°C to 65°C	Capacitance range ESR	Within 30% of the value at 25°C Less than 2 times of the initial specified value
High Temperature Loaded	The specifications shall be met after rated voltage applied at 65°C for 1000 hours	Capacitance range ESR	Within 30% of the initial value Less than 2 times of the initial specified value
High Temperature Storage	The specifications shall be met after storage at 65°C for 1000 hours	Capacitance range ESR	Within 30% of the initial value Less than 2 times of the initial specified value
Cycle Life	The specifications shall be met after 500,000 cycles at 25°C, cycle of charge/discharge from V _R	Capacitance range ESR	Within 30% of the initial value Less than 2 times of the initial specified value

Dimensions

mm

	<table border="1"> <tr> <td>ΦD</td><td>8</td><td>10</td><td>12</td><td>12.5</td><td>16</td><td>18</td></tr> <tr> <td>p</td><td>3.5</td><td colspan="3">5.0</td><td colspan="2">7.5</td></tr> <tr> <td>Φd</td><td>0.6</td><td colspan="3">0.6</td><td colspan="2" rowspan="2">0.8</td></tr> <tr> <td>α</td><td>1.5</td><td colspan="5">2.0</td></tr> </table>	ΦD	8	10	12	12.5	16	18	p	3.5	5.0			7.5		Φd	0.6	0.6			0.8		α	1.5	2.0				
ΦD	8	10	12	12.5	16	18																							
p	3.5	5.0			7.5																								
Φd	0.6	0.6			0.8																								
α	1.5	2.0																											



SRL Series 2.7V -40~+70°C

Standard Ratings for SRL Series

U _R (Surge Voltage) Code	Rated Cap. 25°C,	Impedance		Leakage Current (72hrs)	Size ΦDxL	Weight	P/N
		ESR _{DC}	ESR _{AC} (1KHz)				
(v)	(F)	(mΩ)	(mΩ)	(mA)	(mm)	(g)	-
2.7 (2.85) 2R7	1	400	200	0.008	8 x 14	0.8	SCCDLR2R7105QRH080014E
	2	250	130	0.010	8 x 14	1	SCCDLR2R7205QRH080014E
	3	150	80	0.012	8 x 20	1.4	SCCDLR2R7305QRH080020E
	3.3	150	80	0.014	8 x 20	1.5	SCCDLR2R7335QRH080020E
	5	130	70	0.016	10 x 20	2.1	SCCDLR2R7505QRH100020E
	7	80	55	0.020	10 x 25	2.3	SCCDLR2R7705QRH100025E
	10	60	40	0.030	10 x 30	3.2	SCCDLR2R7106QRH100030E
	10	60	40	0.030	12.5 x 25	3.5	SCCDLR2R7106QRH125025E
	25	35	25	0.080	16 x 25	7	SCCDLR2R7256QRH160025E
	50	22	15	0.140	18 x 40	12.8	SCCDLR2R7506QRH180040E
	60	22	15	0.140	18 x 40	13	SCCDLR2R7606QRH180040E
	70	20	14	0.160	18 x 50	15	SCCDLR2R7706QRH180050E
	100	18	12	0.180	18 x 60	20	SCCDLR2R7107QRH180060E

All product specifications are subject to change without notice (2019E1)